

SG100-2 Silicone Sealing grease

Product features:

- Good lubricity and durable lubrication in wet environment.
- Excellent waterproof seal, water scour resistance;
- Good pressure resistance, non curing, insoluble and non dispersive;
- Good high and low temperature properties, chemical stability and colloid stability;
- Strong material adaptability, good compatibility with all kinds of plastics and metal;
- Non-toxic, tasteless, no irritation, fully meet the requirements of environmental protection;

Product Specification:

- Base oil: modified silicone oil
- Thickener: inorganic thickener

Application scope:

- it is used for the lubrication and sealing of various kinds of food machinery parts.
- for all kinds of kitchen small electrical components, the lubrication and sealing of electronic products;
- used for the lubrication and seal of all kinds of children's toy parts;
- for all kinds of kitchen and toilet facilities - the lubrication and seal of the sprinkler, faucet, water valve, water heater and so on;
- it is used to lubricate and protect the surface of plastic parts in every environment, and to lubricate and seal metal and rubber, metal and polymer sliding parts.

Technical parameter:

Item	SG100-2	Test method (ASTM #)
Color	White translucent	visually
NLGI	2#	D217
Worked penetration, 25℃, 0.1mm	265~295	D217
Drop point, ℃	/	D566
Drop point, ℃	1.2	D972
Run off (100℃/24h) , %	4.0	D1742
Corrosion test of copper sheet (100℃, 24h)	1a	D4048
Work temperature℃	-40~200℃	--



Packing specifications

1KG/drum, 5KG/drum, 15KG/drum

How to use

The use of traditional grease, such as Clean brush, grease gun, manual or automatic Distribution equipment. Ensure lubrication before adding grease. The cleaning and drying of the surface of the parts to ensure the injection of fat. The process is clean..

Storage and validity

At the temperature of 40 C (104 F) or below, the original unsealed package, from the date of production, the quality of this product is 36 months.

Use restrictions

This product is not tested or stated as suitable for medical or medical use.

Limited Guarantee Information

This file data, according to our understanding, is true and accurate. However, due to the conditions and methods of use of our products we cannot control, this information can not replace the effective customer to ensure product safety, can only, and fully meet the specific end use, and we recommend the use of the test. Provided, shall not be regarded as infringement of any patent right cause.

For details, please log in

ww.vnovo.cn or consult you as A distributor or sales representative of the land..

Technical support:

sales@vnovo.cn