

Tectyl Cool 290V

Introduction

Tectyl Cool 290V is good for middle and heavy duty cutting with its good lubrication for longer tool life and improved surface illumination of processed parts.

In Addition, Tectyl Cool 290V exhibits excellent bio-stability, rust protection and de-foaming property. Its good tramp oil rejection allows to keeping the workshop clean and the longer coolant life.

Features

- Excellent machining Capabilities
- Long Sump Life
- Excellent corrosion protection
- Low foaming
- Clean running

Benefits

- Increased tool life; improves surface finish
- Reduced disposal cost and prolonged exchange period
- In-processes protection of machinery and parts
- Improved working atmosphere
- Keep shop areas clean

Typical physical Properties

Appearance	(Neat)	: Amber Liquid
	(3% Solution)	: Translucent White
pH	(3% Solution)	: 9.2
Emulsion stability		: Pass
Factor		: 1.3

- Above is typical data on fresh oil obtained at our laboratory.
- Hocut 290 is free of nitrite, sulfur, secondary amines, and chlorinated EP additives.

Recommended Concentration

- | | | |
|-------------|--------------|----------|
| ● Machining | (Medium) | 4 ~ 5 % |
| | (Heavy Duty) | 6 ~ 12 % |
| ● Grinding | | 3 ~ 5 % |

Storage

- Handling : Avoid Squirts When Decanting, Keep drum closed When not in use.
- Storage : from 50°C to 40°C, 6months, do not store at a higher temperature than 70 °C.

Packing

Tectyl Cool 290V is shipped in 53 gallon (U.S.) steel drums (200 liter) and in bulk.

KOREA HOUGHTON CORPORATION

19th Floor, KSCFC Bldg. 395-70, Shindaebang-Dong, Dongjak-Ku, Seoul, KOREA

TEL : (02) 3284-3300, 3354, 3355, 3363, 3369 / FAX : (02) 3284-3333~5 / www.houghton.co.kr



ISO 14001 인증



ISO/TS16949인증