



H-TECH 100 Plus 5W-30

Fuel Economy Gasoline & Diesel Engine Oil

100% Synthetic

TYPE OF USE

Designed for fuel economy performance and provide ultimate level of power especially for recent gasoline engine designs. Can also be used on diesel engines requiring API CF oils. Suitable for turbo or naturally aspirated gasoline engines, equipped with catalytic converters.

Suitable for all gasoline engines using leaded or unleaded gasoline, LPG, Autogas fuel. E85 fuel compatible.

All driving conditions : City, Road, Highway.

PERFORMANCE

STANDARDS ILSAC GF-5
API SN with CF performance

Designed to meet the new ILSAC GF-5 and API SN specifications. Provides exceptional engine protection and at the same time even more efficient operation. Improved fuel economy and greater power when compared to more viscous products.

Formulated with latest technology to ensure emission control systems durability. The high performance anti-wear additive results in reduction of engine internal frictions and increases engine life duration by reducing wear.

Excellent anti-oxidation preventing premature oil thickening and ageing due to thermal stress.

Very efficient anti-deposit and anti-black sludge power which maintains a clean engine.

Anti-corrosion, Anti-foam properties.

RECOMENDATIONS

Drain period : according to manufacturers' recommendations and driving patterns.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D4052	0.849
Viscosity at 40°C (104°F)	ASTM D445	62.9 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.2 mm ² /s
Viscosity index	ASTM D2270	149
TBN	ASTM D2896	7.3 mg KOH/g