

---

# XR 212-68

## Refrigeration Lubricant

---

### Product Descriptions

XR 212-68 is a high performance refrigeration compressor lubricant based on a premium naphthenic mineral oil. The excellent stability and low temperature properties make this product ideal for a wide variety of refrigeration applications. XR 212-68 is wax free which prevents solid formation in the evaporator and expansion valve.

### Applications\*

- R-22
- R-123
- R 414A

*\*To assure proper lubricant selection, please consult your Xaerus Performance Fluids representative.*

### Packaging

- 5 US Gallon
- 55 US Gallon
- IBC - Totes

## Physical Properties

Criteria	Value	Method
Viscosity cSt @ 40° C	67.7	ASTM D-445
Viscosity cSt @ 100° C	7.0	ASTM D-445
Viscosity Index	37	ASTM D2270
Moisture, ppm	< 50	ASTM D-1744
Specific Gravity @ 60°F/15.6° C	0.909	ASTM D-4052
Density, lb/gal	7.58	ASTM D-4052
Flash Point, °F/°C	206	ASTM D-92
Pour Point, °F/°C	-30	ASTM D-97
Color	0.5	ASTM D-1500
Aniline Point, °F/°C	194/90	ASTM D-611

*Notice: Physical Properties are typical of those obtained with normal production tolerances and do not constitute specifications.*

## Health and Safety

Based on available information, XR 212-68 is a non-toxic, non-hazardous product that is not expected to cause any adverse health effects when used as designed. Users are advised to follow the recommendations provided in the SDS.

### **Xaerus Corporate Center / Distribution Center**

2825 Schuette Rd.

Midland, MI 48642 USA

Phone: 1-989-486-8330 Email: [sales@xaerusfluids.com](mailto:sales@xaerusfluids.com)