(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017

Page 1 of 8 Print date: 12/06/2017

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Product Code: BESLUX GEAR-ATOX 220 11001

1.2 Relevant identified uses of the mixture and uses advised against.

Gear oil

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	BRUGAROLAS, S.A.
Address:	Camí de la Riera 36-44 P.I. Cova Solera
City:	08191 Rubí
Province:	Barcelona
Telephone:	+34935883100
Fax:	+34935883101
E-mail:	h-seguridad@brugarolas.com
Web:	www.brugarolas.com

1.4 Emergency telephone number: +34935883100 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

H statements: H412

Harmful to aquatic life with long lasting effects.

P statements:

P273 Avoid release to the environment. P501 Dispose content and container as dangerous waste.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2

Revision date: 12/06/2017

Page 2 of 8 Print date: 12/06/2017

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
CAS No: 128-37-0 EC No: 204-881-4 Registration No: 01- 2119565113-46-XXXX	[1] 2,6-di-tert-butyl-p-cresol	0,25 - 1 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 (M=1)	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2

Revision date: 12/06/2017

Page 3 of 8 Print date: 12/06/2017

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited. Follow legislation on occupational health and safety. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35 °C, in a dry and wellventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Industrial and professional use, described in 1.2.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017

Page 4 of 8 Print date: 12/06/2017

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
2,6-di-tert-butyl-p-cresol	128-37-0	United	Eight hours		10
		Kingdom [1]	Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
2,6-di-tert-butyl-p-cresol	DNEL	Inhalation, Long-term, Systemic effects	3,5
CAS No: 128-37-0	(Workers)		(mg/m ³)
EC No: 204-881-4			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: OILY LIQUID Colour (*): COLOURLESS Odour: ODOURLESS pH: N/A Freezing point: <-12 °C Boiling point: >300 °C Flash point: >245 °C Relative density: 0,8700 g/cm³ at 20 °C Hydrosolubility: INSOLUBLE Auto-ignition temperature: >325 °C

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Kinematic viscosity: 220 cSt at 40 °C Kinematic viscosity: 21,2 cSt at 100 °C

(*) Due to the characteristics of the product may have slight variations in its colour tone.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017 Page 5 of 8 Print date: 12/06/2017

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

At high temperatures can occur pyrolysis and dehydrogenation.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product. Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin. Splatters in the eyes can cause irritation and reversible damage.

Non-toxic product, category NSF H-1. Suitable for incidental food contact.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Not conclusive data for classification.

c) serious eye damage/irritation; Not conclusive data for classification.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017

Page 6 of 8 Print date: 12/06/2017

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017 Page 7 of 8 Print date: 12/06/2017

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description: ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous. ICAO/IATA: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

(in accordance with Regulation (EU) 2015/830)

11001-BESLUX GEAR-ATOX 220



Version: 2 Revision date: 12/06/2017 Page 8 of 8 Print date: 12/06/2017

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, category 1 Aquatic Chronic 3 : Chronic effect to the aquatic environment, category 3

Sections changed compared with the previous version: 1,3,8,9,10,11,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.