



Sullair Performance Lubricant

SULLUBE®

Genuine Sullube for Stationary Compressors



An extended-life, polyglycol base, synthetic fluid for stationary rotary screw compressors, Sullube has been used in more than 50,000 compressors with more than 150 million annual operating hours with virtually no unscheduled downtime from lubricant failure.

- One of the longest useful lives in the industry — up to 10,000 hours
- Resists sludge and varnish
- Removes existing varnish
- High flash point
- High thermal conductivity
- Environmentally friendly

Unmatched performance. Exceptional value.

Advanced formulation powered by Dow Technology, Genuine Sullube is the standard factory fill for Sullair stationary air compressors. Proven for more than a quarter-century, this long-lasting fluid costs less per hour over your equipment's life. It also prevents the formation of varnish — the leading cause of air end failure — and keeps your compressors running exceptionally clean and cool. Sullube delivers the best formula blend and additive package on the market, supported by exceptional quality control and ingredient consistency. Regular use of Sullube will protect and maintain your Sullair factory warranty.

Since Sullube is compatible with the common elastomers found in compressor seals, hoses and solenoids, compressors from many manufacturers can be converted to Sullube.

FEATURES AND BENEFITS

Protects and cleans

Sullube prevents varnish and sludge buildup and even removes existing varnish. A flush conversion will remove varnish, thus reducing energy demand, improving cooling, and extending air-end life.

Reduces fluid Loss

Low carryover (less than 1 ppm) means less fluid is needed for top-off.

Promotes safety

With a high flash point (505°F/263°C) and good cooling ability, Sullube promotes reliable and safe operation.

Kind to the environment

Sullube in-compressor condensate is biodegradable, saving time and expense in condensate handling and disposal.

Cools efficiently

High thermal conductivity dissipates heat, helping your compressors run cooler in any climate. It also helps stabilize operating temperature.

Lubricates effectively

With a high viscosity index, Sullube provides excellent film thickness, keeping bearings well lubricated even at temperatures to 200°F (93°C).

Comprehensive support

Sullair and our distributors stand ready with fluid professionals who can help you with any Sullube-related issues or questions. Our exclusive Compressor Fluid Analysis program helps you evaluate your fluid and provides data to support your lubricant performance history, changeout intervals, and environmental conditions that may affect your fluid.

PRODUCT INFORMATION



PACKAGING	
Size	Part Number
5 Liter	02250181-422
5 Gallon	250022-669
55 Gallon	250022-670

TYPICAL PROPERTIES		
Viscosity	104°F (40°C)	39.3
	212°F (100°C)	7.3
Flash Point	505°F (263°C)	
Hours	10,000	



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



SULLAIR.COM   