

# SAFETY DATA SHEET

Revision date: 2024-07-02

Version: 20240228\_5073.0

## 1. IDENTIFICATION

- A. Product name** : ZIC X9000 10W-40 (MZIC X9000 10W-40)
- B. Recommended use and restriction on use**
- **General use** : Lubricants
  - **Restriction on use** : Use only for lubricants
- C. Manufacturer / Supplier / Distributor information**
- Manufacturer information**
- **Company name**  
SK Enmove Co., Ltd.
  - **Address**  
26, Jong-ro, Jongno-gu, Seoul, Korea
  - **Dept.**  
Global Tech. Solutions
  - **Telephone number** : +82-2-2121-6114
  - **Emergency telephone number**  
+82-2-2121-6114
  - **Fax number** : +82-2-2121-2601
  - **E-mail address** : safetyservice@sk.com
- Supplier/Distributor information**
- **Company name**  
SK Enmove Co., Ltd.
  - **Address**  
26, Jong-ro, Jongno-gu, Seoul, Korea
  - **Dept.**  
Global Tech. Solutions
  - **Telephone number** : +82-2-2121-6114
  - **Emergency telephone number**  
+82-2-2121-6114
  - **Fax number** : -
  - **E-mail address** : safetyservice@sk.com

## 2. HAZARD IDENTIFICATION

- A. GHS Classification**
- Not applicable
- B. GHS label elements**
- Hazard symbols**
- Not applicable
- Signal words**
- Not applicable
- Hazard statements**
- Not applicable
- Precautionary statements**
- 1) Prevention**
    - Not applicable
  - 2) Response**
    - Not applicable
  - 3) Storage**
    - Not applicable
  - 4) Disposal**
    - Not applicable

### C. Other hazards which do not result in classification : (NFPA Classification)

#### ○ NFPA grade (0 ~ 4 level)

- Health : 0, Flammability : 1, Reactivity : 0

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	%[weight]
C14-16-18 Alkyl phenol		-	$\geq 0.1, < 1$
Phosphorodithioic acid O,O-dialkyl(C=3-14) esters zinc salts		134759-18-5	$\geq 0.1, < 1$
ar-Nonyl-N-(nonylphenyl)benzenamine		36878-20-3	$\geq 1, < 5$
Distillates (petroleum), hydrotreated heavy paraffinic	Emulsifiable oil	64742-54-7	$\geq 60, < 70$
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Heavy paraffinic base lube stock ; Mineral oil, petroleum distillates, solvent dewaxed heavy paraffinic (severe solvent-refining and/or hydrotreatment) ; Solvent dewaxed heavy paraffinic distillate ; Adriatic spindle oil	64742-65-0	$\geq 5, < 15$

## 4. FIRST AID MEASURES

### A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15 minutes and call a doctor/physician.

### B. Skin contact

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Wash contaminated clothing thoroughly before re-using.

### C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.

### D. Ingestion contact

- Please be advised by doctor whether induction of vomit is demanded or not.
- Rinse your mouth with water immediately.

### E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

### F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

## 5. FIREFIGHTING MEASURES

### A. Suitable (Unsuitable) extinguishing media

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

### B. Specific hazards arising from the chemical

- Not available

### C. Special protective actions for firefighters

- Cool containers with water until well after fire is out.
- Keep unauthorized personnel out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- Notify your local firestation and inform the location of the fire and characteristics hazard.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.

## 6. ACCIDENTAL RELEASE MEASURES

### A. Personal precautions, protective equipment and emergency procedures

- Ventilate closed spaces before entering.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Handle the damaged containers or spilled material after wearing appropriate protective equipment
- Do not direct water at spill or source of leak.

## B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

## C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.

## 7. HANDLING AND STORAGE

### A. Precautions for safe handling

- Wash thoroughly after handling.
- Avoid contact with incompatible materials.
- Dealing only with a well-ventilated place.
- Do not handle until all safety precautions have been read and understood.
- Do not inhale the steam prolonged or repeated.

### B. Conditions for safe storage, including any incompatibilities

- Check regularly for leaks.
- Do not apply direct heat.
- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Prevent static electricity and keep away from combustible materials or heat sources.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### A. Exposure limits

#### ○ ACGIH TLV

- [Distillates (petroleum), hydrotreated heavy paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : TWA 5 mg/m<sup>3</sup>, Inhalable particulate matter(Mineral oil, Pure, highly and severely refined)

#### ○ OSHA PEL

- Not available

### B. Engineering controls

- Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

### C. Individual protection measures, such as personal protective equipment

#### ○ Respiratory protection

- Respiratory protection is ranked in order from minimum to maximum.
- Consider warning properties before use.
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vaporcartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.

#### ○ Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

#### ○ Hand protection

- Wear appropriate glove.

#### ○ Skin protection

- Wear appropriate clothing.

#### ○ Others

- Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>A. Appearance</b>	
- Appearance	: Liquid
- Color	: Transparent Brown
<b>B. Odor</b>	: Mild petroleum odor
<b>C. Odor threshold</b>	: Not available
<b>D. pH</b>	: Not available
<b>E. Melting point/Freezing point</b>	: Not available
<b>F. Initial Boiling Point/Boiling Ranges</b>	: > 300 °C
<b>G. Flash point</b>	: 232°C (COC)
<b>H. Evaporation rate</b>	: Not available
<b>I. Flammability(solid, gas)</b>	: Not available
<b>J. Upper/Lower Flammability or explosive limits</b>	: Not available
<b>K. Vapour pressure</b>	: ≤ 0.1 kPa (20 °C)
<b>L. Solubility</b>	: Not available
<b>M. Vapour density</b>	: ≥ 5 (Air = 1)
<b>N. Specific gravity(Relative density)</b>	: 0.86 g/cm <sup>3</sup> (15°C)
<b>O. Partition coefficient of n-octanol/water</b>	: Not available
<b>P. Autoignition temperature</b>	: Not available
<b>Q. Decomposition temperature</b>	: Not available
<b>R. Viscosity</b>	: 91 mm <sup>2</sup> /s (40°C)
<b>S. Molecular weight</b>	: Not available

## 10. STABILITY AND REACTIVITY

### A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

### B. Possibility of hazardous reactions

- Hazardous Polymerization will not occur.

### C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces

### D. Incompatible materials

- Not available

### E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

## 11. TOXICOLOGICAL INFORMATION

### A. Information on the likely routes of exposure

#### ○ (Respiratory tracts)

- Not available

#### ○ (Oral)

- Not available

#### ○ (Eye-Skin)

- Not available

### B. Delayed and immediate effects and also chronic effects from short and long term exposure

#### ○ Acute toxicity

##### \* Oral

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rat (Read-across 64742-56-9) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 5000 mg/kg Rat (IUCLID), LD50 > 5000 mg/kg Rat (Read-across 64742-56-9) (ECHA)

##### \* Dermal

- Product (ATEmix) : >5000mg/kg
- [Distillates (petroleum), hydrotreated heavy paraffinic] : LD50 > 5000 mg/kg Rabbit (Read-across 64742-56-9) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LD50 > 2000 mg/kg Rabbit (IUCLID), LD50 > 5000 mg/kg Rabbit (Read-across 64742-56-9) (ECHA)

##### \* Inhalation

- Product (ATEmix) : 2.0mg/L < ATEmix <= 10.0mg/L
- [Distillates (petroleum), hydrotreated heavy paraffinic] : Mist LC50 > 5.53 mg/L 4 hr, Rat, Read-across : CAS No. 64741-88-4 (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Mist LC50 > 5.53 mg/L 4 hr, Rat (Read-across) (OECD TG 403) (ECHA)

**Skin corrosion/irritation**

- Not available

**Serious eye damage/irritation**

- Not available

**Respiratory sensitization**

- Not available

**Skin sensitization**

- Not available

**Carcinogenicity**

\* **IARC**

- Not available

\* **OSHA**

- Not available

\* **ACGIH**

- Not available

\* **NTP**

- Not available

\* **EU CLP**

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Carc. 1B (Note L)  
It is not considered carcinogenic. It has been demonstrated to contain less than 3% extractables by the IP 346 test (EU CLP Note L)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Carc. 1B (Note L)  
It is not considered carcinogenic. It has been demonstrated to contain less than 3% extractables by the IP 346 test (EU CLP Note L)

**Germ cell mutagenicity**

- Not available

**Reproductive toxicity**

- Not available

**STOT-single exposure**

- Not available

**STOT-repeated exposure**

- Not available

**Aspiration hazard**

- Not available

## 12. ECOLOGICAL INFORMATION

### A. Ecotoxicity

**Fish**

- [Distillates (petroleum), hydrotreated heavy paraffinic] : LL50 > 100 mg/L, 96hr, Pimephales promelas (Read-across) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : LC50 5000 mg/l 96 hr Oncorhynchus mykiss (IUCLID), LL50 > 100 mg/L, 96hr, Pimephales promelas (Read-across) (ECHA)

**Crustaceans**

- [Distillates (petroleum), hydrotreated heavy paraffinic] : EL50 > 10000 mg/L, 48hr, Daphnia magna (Read-across), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/l 48 hr Daphnia magna (IUCLID), EL50 > 10000 mg/L 48 hr Daphnia magna (Read-across) (OECD TG 202), NOEL 10 mg/L 21 d Daphnia magna (Read-across 64742-53-6) (OECD TG 211, GLP) (ECHA)

**Algae**

- [Distillates (petroleum), hydrotreated heavy paraffinic] : EC25 1152.9 mg/L, 96hr, Pseudokirchneriella subcapitata, NOEL >= 100 mg/L, 72hr (Read-across 72623-87-1) (OECD TG 201) (ECHA)
- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : EC50 1000 mg/l 96 hr Scenedesmus subspicatus (IUCLID), EC25 1152.9 mg/L 96hr, NOEL >= 100 mg/L 72hr Pseudokirchneriella subcapitata (Read-across 72623-87-1) (OECD TG 201) (ECHA)

### B. Persistence and degradability

**Persistence**

- Not available

**Degradability**

- Not available

**C. Bioaccumulative potential**

**Bioaccumulative potential**

- Not available

**Biodegradation**

- [Distillates (petroleum), hydrotreated heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O2 consumption) (Read-across) (OECD TG 301 F, GLP) (ECHA)

- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : Not readily biodegradable, 31 % 28 d (O2 consumption) (Read-across) (OECD TG 301 F, GLP) (ECHA)

**D. Mobility in soil**

- Not available

**E. Other adverse effects**

- Not available

### 13. DISPOSAL CONSIDERATIONS

**A. Disposal methods**

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.

- If water separation is possible, pre-process with Water separation process.

- Dispose by incineration.

**B. Special precautions for disposal**

- The user of this product must dispose by oneself or entrust it to a waste disposer, a person who recycles other's waste or establishes and operates waste disposal facilities.

- Dispose of waste in accordance with all applicable laws and regulations.

### 14. TRANSPORT INFORMATION

**A. UN No. (IMDG CODE/IATA DGR)**

- Not applicable

**B. Proper shipping name**

- Not applicable

**C. Hazard Class**

- Not applicable

**D. IMDG CODE/IATA DGR Packing group**

- Not applicable

**E. Marine pollutant**

- Not applicable

**F. Special precautions for user related to transport or transportation measures**

- Local transport follows in accordance with Dangerous goods Safety Management Law.

- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.

- EmS FIRE SCHEDULE : Not available

- EmS SPILLAGE SCHEDULE : Not available

- Air transport(IATA): Not subject to IATA regulations.

### 15. REGULATORY INFORMATION

**A. National and/or international regulatory information**

**POPs Management Law**

- Not applicable

**Information of EU Classification**

\* Classification

- [Distillates (petroleum), hydrotreated heavy paraffinic] : H350

It is not considered carcinogenic. It has been demonstrated to contain less than 3% extractables by the IP 346 test (EU CLP Note L)

- [Distillates (petroleum), solvent-dewaxed heavy paraffinic] : H350

It is not considered carcinogenic. It has been demonstrated to contain less than 3% extractables by the IP 346 test (EU CLP Note L)

**U.S. Federal regulations**

**\* OSHA PROCESS SAFETY (29CFR1910.119)**

- Not applicable

**\* CERCLA Section 103 (40CFR302.4)**

- Not applicable

**\* EPCRA Section 302 (40CFR355.30)**

- Not applicable

**\* EPCRA Section 304 (40CFR355.40)**

- Not applicable

**\* EPCRA Section 313 (40CFR372.65)**

- Not applicable

**Rotterdam Convention listed ingredients**

- Not applicable

**Stockholm Convention listed ingredients**

- Not applicable

**Montreal Protocol listed ingredients**

- Not applicable

## 16. OTHER INFORMATION

**A. Reference**

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.

- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

**B. Issue date**

2024-07-02

**C. Revision number and Last date revised**

Revision number : 0

Last date revised : 2024-07-02

**D. Other**

- This SDS is prepared according to the Globally Harmonized System (GHS).