

# [Material Safety Data Sheet]

#### SECTION 1 PRODUCT

Product Name Sinopec Moly-Lithium Grease NLGI 3

Product Code 60090044

Product Usage Suitable for lubricating the parts such as bearings, gears and coupling of high load

mechanical equipment.

# SECTION 2 COMPOSITION/ INFORMATION ON INGREDIENTS

#### This material is a mixture.

COMPONENTS	CAS NUMBER	AMOUNT
Thickener	Mixture	6-15% weight
Additive	Mixture	<14% weight
Base oil	Mixture	75-90% weight

#### **SECTION 3 HAZARDS IDENTIFICATION**

Potential health effects

The International Agency for Research on Cancer (IARC) has determined there is sufficient evidence for the carcinogenicity in experimental animals of used the oil. Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eyes, skin or respiratory irritation.

# **SECTION 4 FIRST AID MEASURES**

Eye Flush with water for 15 minutes. If irritation occurs, get medical attention.

Skin Flush skin with water, and then wash with soap and water. Get medical attention.

Inhalation Remove victim to fresh air and provide oxygen. Get medical attention.

Ingestion Do not induce vomiting. Get medical attention.

#### **SECTION 5 FIRE FIGHTING MEASURES**

Extinguishing media Carbon dioxide, foam, dry chemical and water fog.

Extinguishing Method Spray

Combustion products

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition

products, in the case of incomplete combustion.

Forbidden media Water

Moly-Lithium Grease NLGI 3 1 of 4 MSDS: 60090044 CN Revision Number: 1 Revision Date: June 19, 2013



#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

Protective Measures Wear appropriate personal protective equipment when cleaning up spills.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

Spill Management FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other

suitable material. Place in non-leaking container and seal tightly for proper disposal.

# **SECTION 7 HANDLING AND STORAGE**

Storage Do not store in open or unlabeled containers. Store in a cool, dry place with adequate

ventilation. Keep away from open flames and high temperatures.

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT

Empty container warning PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH

CONTAINERS TO HEAT, FLAME.

#### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure controls

Provide adequate ventilation to control airborne concentrations below the exposure

guidelines/limits.

Respiratory Protection If engineering controls do not maintain airborne concentrations to a level which is

adequate to protect worker health, an approved respirator must be worn.

Eye Protection Chemical Goggles, or Safety glasses with side shields.

Hand Protection Use protective gloves which is chemically resistant to this material.

Personal protection Use protective clothing and shoes which are chemically resistant to this material.

Note to sanitation Wash hands with water an use cosmetic to protect.

# SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black smooth buttery
Odor No peculiar smell

Worked NO.3

Cone Penetention,0.1mm 220∼250

Dropping Point, ℃ >185

#### SECTION 10 STABILITY AND REACTIVITY

Stability Stable (at room temperature)

Conditions and materials to

avoid

Extreme heat and high energy sources of ignition and strong oxidizers.

Hazardous decomposition

product

Product does not decompose at ambient temperatures.

Hazardous polymerization Will not occur.

Moly-Lithium Grease NLGI 3 2 of 4 MSDS: 60090044 CN Revision Number: 1 Revision Date: June 19, 2013



#### **SECTION 11 TOXICOLOGICAL INFORMATION**

ORAL TOXICITY (RATS): Practically low toxic (LD50: greater than 5000mg/kgBW). —

Based on testing of similar products and/or the components.

Acute Toxicity

INHALATION TOXICITY (RATS): Practically low toxic (LC50: greater than

10000mg/m3). —Based on testing of similar products and/or the components.

#### **SECTION 12 ECOLOGICAL INFORMATION**

Ecological toxicity Though long time infiltration, it may produce ecological toxicity.

When released into the environment, adsorption to sediment and soil will Be the Mobility

predominant behavior.

Persistence and degradability This product is expected to be inherently biodegradable.

Bioaccumulation is unlikely due to the very low water solubility of this product; therefore

bioavailability to aquatic organisms is minimal.

#### SECTION 13 DISPOSAL CONSIDERATIONS

Product is suitable for burning in an enclosed, controlled burner for fuel value. In

Waste disposal addition, the product is suitable for processing by an approved recycling facility or can

be disposed of at an appropriate government waste disposal facility.

Use protection things ,including protection gloves, glasses and respirator, because Note to release

explosion may happen heating in the container.

#### **SECTION 14 TRANSPORT INFORMATION**

Transport The transport department work abiding by all the law ,rule and regulations.

# **SECTION 15 REGULATORY INFORMATION**

National regulation Solid waste pollution prevention and cure law of The People's Republic of China.

State Regulation Water pollution standard of local government.

#### **SECTION 16 OTHER INFORMATION**

Other data Get information and manual from the market department or technology department.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Moly-Lithium Grease NLGI 3 3 of 4 MSDS: 60090044 CN Revision Number: 1 Revision Date: June 19, 2013