



SHL SYN COMP 46

Application SHL SYN COMP 46 is a unique high performance additive systems and advanced synthetic base oils that contain rotary vane screw type
 The compressor is designed only oil products.
 SHL SYN COMP 46 product is a screw rotary vane compressor-only product.
 Such as high-temperature and high-pressure multi-stage compressor available for use in all facilities.

- Properties /Benefits**
- Excellent foaming inhibitory.
 - Outstanding oxidation stability.
 - Excellent incompressible and corrosion resistance.
 - Remarkable demulsibility ensuring rapid water separation.
 - Excellent wear resistance.

- Handling /Package**
- Drum Feel free to keep in direct sunlight indoors.
 Please keep written a cover on top when outdoors for more details, please refer to the MSDS.
- 200L Drum
 - 20L Pail

Physical properties

Test Item	Test Method	Results
Specific gravity (15/4°C)	KSM 2002	0.859
Kinematic Viscosity (40°C, cSt)	KSM 2014	46
Viscosity Index (VI)		160
Flash point (°C)	KSM 2010	250
Pour Point (°C)	KSM 2016	--30
Copper Corrosion (100°C/3hrs)	KSM 2018	1
Oxidation's stability (RBOT 150°C min)	KSM ISO 2160	800
Demulsibility Characteristic min @54°C	KSM ISO 6614	40-40-0(10)